



SPOA10 SERIES TWO POST LIFTS

10,000 lbs. CAPACITY / ASYMMETRIC LIFTS



MODEL SHOWN:
SPOA10N800BL

Rotary's versatile asymmetric two-post lift is the only lift you'll ever need.

With options at every turn, you can customize the SPOA10 series to fit the needs of your shop.

Choose your:

- Arm configuration
- Adapter type
- Lift height
- Power option
- Productivity accessories

Lifts feature:

- Original "Double S" column design
- Performance tested to 20,000 cycles
- Nationwide support
- ALI Gold Certified

SPOA10 TRIO™

Includes TRIO™ 2-piece, three-stage arms with the choice of adapter options

Patented two-piece, three-stage TRIO™ asymmetrical arms have a lower profile making spotting a vehicle fast and easy with better vehicle protection. The arms are lower than the adapters providing clearance for vehicle panels and ground effects. Choose the best adapter set for each vehicle to be repaired all on the same arm.†



SPOA10-FA-TRIO SPOA10-TA-TRIO SPOA10-RA-TRIO
† EACH ADDITIONAL ADAPTER SET IS SOLD SEPARATELY

ASYMMETRIC LIFT SPECIFICATIONS WITH SHOCKWAVE

- Overall Height:** 11' 8-1/2" / 12' 4-1/2"
- Overall Width:** 11' 5-3/8"
- Drive-thru:** 95 1/4"
- Inside Columns:** 107 1/4"
- Min. Bay Size:** 12' x 24"
- Ceiling Height Min:** 12' / 12' 6"
- Motor / Voltage 10:** 2 HP, 208-230V / 5 HP, 110V*
- Time of Full Rise and Descent:** 45 seconds / 40 seconds
25 seconds / 19 seconds*

* Actual rise and descent times vary depending on vehicle weight.

SPOA10

Standard 2-stage arms with exclusive three-position flip-up FA adapters

Flip-up adapters feature great strength in a simple design. The entire assembly is joined with a single pin providing stable support in any position.



Select product photography is shown with optional accessories that are not standard with each lift purchase.

SPOA10 SERIES LIFTS

ARE AVAILABLE WITH SHOCKWAVE-EQUIPPED POWER

SHOCKWAVE™ DC power with onboard 110v charger provides 2X the lifting speed of conventional lifts.



SCAN THIS VIDEO CODE TO LEARN ABOUT THE BENEFITS OF ROTARY SHOCKWAVE LIFTS

ASYMMETRIC LIFT MODELS

BL = Blue / RD = Red

	STANDARD	SPOA10N700BL SPOA10N700RD	SPOA10N800BL SPOA10N800RD	SPOA10N8T0BL SPOA10N8T0RD	SPOA10N8G0BL SPOA10N8G0RD
Rise*	STANDARD SHOCKWAVE	72 3/4" - 78 3/8" 75 3/4" - 81 3/8"	72 3/4" to 78 3/8" 75 3/4" to 81 3/8"	72 1/8" to 73 3/8" 75 1/8" to 76 3/8"	72 1/16" to 73 5/16" 75 1/16" to 76 5/16"
Front Arm Min/Max		20 1/2" - 40 3/4"	21 1/4" / 43 1/2"	20 1/2" / 40 3/4"	20 1/2" / 40 3/4"
Rear Arm Min/Max		40 1/4" - 60 7/8"	32 3/4" / 61"	34 1/2" / 58 1/4"	34 1/2" / 58 1/4"
Min Adapter Height		4 3/4"	4 3/4"	4 1/8"	4 1/16"

* Rise measures lowest and highest position of the supplied adapters from floor to full cylinder stroke. Heights and widths reflect standard settings. SPOA10 lift colors come standard with your choice of red or blue.

Rotary Lift

2700 Lanier Drive / Madison, IN 47250, USA

rotarylif.com



Lit# Rotary SPOA10 Cutsheet.2021.011

©2021 VEHICLE SERVICE GROUP™, Printed in U.S.A., All Rights Reserved. Unless otherwise indicated, ROTARY, VEHICLE SERVICE GROUP™, DOVER and all other trademarks are property of Dover Corporation and its affiliates.

North / South America Information

Sales: 800.445.5438
insidesales@vsgdover.com

Tech. Support: 800.445.5438
technicalsupport@rotarylif.com

Government Sales: 800.445.5438 X5655

For additional information: rotarylif.com/Government-Purchasing-Assistance/

Product specifications, part numbers, images and component descriptions are subject to change without notice or liability.

Global Contact Information

USA: 1.812.273.1622
Canada: 1.905.812.9920

Latin America / Caribbean: 1.812.273.1622
Brazil: +55.11.4534.1995

